

# HARD FLOOR CLEANER



0,75L

## PRODUCT DESCRIPTION

Hard floor cleaner is a water-based cleaner for removing old layers of polish (hard floor polish & UNICAREX-MATT) from varnished and lacquered floors. Hard floor cleaner can also be used as a degreaser to remove stubborn stains and stripes from lacquered floors.

## TECHNICAL DETAILS

APPEARANCE	TRANSPARANT
VISCOSITY	DUN VLOEIBAAR
DENSITY	1,05
PH VALUE	9
SCENT	FRESH DETERGENT SCENT

## PRE-TREATMENT

Remove any dust before using Hard floor cleaner.

## USER INSTRUCTIONS

### Removing stains and stripes:

Dilute Hard floor cleaner 1:10 in lukewarm water and clean the floor with a mop, microfiber cloth or soft scrubbing brush. After applying, clean the floor with just water.

### Removing layers of polish:

Dilute the Hard floor Cleaner 1:5 in lukewarm water and clean the floor with a soft scrubbing brush or mop. You can also use a floor buffer with a green or red pad. Allow the product to work for some time and then remove the dirt with a squeegee or mop. Afterwards, thoroughly clean the floor with just water.

**IMPORTANT:** a parquet floor must never be too wet, so avoid excess water on the floor.



## DRYING TIME

Allow to work for several minutes, **don't let the product dry up!**



## COVERAGE

+/- 200-400 m<sup>2</sup>/ litre

## AFTER TREATMENT

After applying Hard floor cleaner, you can re-apply Hard floor polish or UNICAREX-MATT on the floor. For regular maintenance of varnished floors, use Ciranova Hard floor fresh.

## PRODUCT INFORMATION

- Shelf life: 18 months in original and unopened container.
- Store under frost-free conditions

## PRODUCT INFORMATION

After use, clean tools with water.

Do not mix with other cleaning products. Keep out of reach of children.

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

## PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare  
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48  
www.ciranova.be ciranova@ciranova.be